

RoClean® 2575

Liquid, acidic cleaner for membranes

Application

RoClean® 2575 is a liquid, acidic membrane cleaner based on inorganic acids. It can be used for the most membrane types on the market.

RoClean® 2575 is especially developed to remove scaling from acid resistance membranes.

RoClean® 2575 is able remove inorganic deposits.

Chemical and physical properties

Characteristics	Data
Colour and appearance:	Clear liquid
Composition:	combination of inorganic acids
pH-Value (1 %, DI-water):	1.3 ± 0.4
Solubility:	water-soluble

Dosage

- Application Concentration : 5 - 10 g/l
- Application Temperature: 25 - 50 °C
- Time of Treatment: 15 - 60 min

Directions of use

For details on membrane cleaning procedures we refer you to our technical information 401.

The make-up concentration and the temperature of RoClean® 2575 is depending on the deposits to remove. General make-up concentration is between 5 and 10 g/l.

The treatment temperature should be between 25°C to 50°C.

Before using RoClean® 2575 consult the instructions of the membrane supplier. Attention should be paid to the permitted pH- and temperature values.

Waste water Information

The product solution has to be neutralized with an alkaline agent previous to its discharge.

Follow the local restrictions for discharging.

Handling Precautions

For information, please see material safety data sheet.

Certification

Our quality management system (ISO 9001), environmental management system (ISO 14001) and occupational health and safety management system (ISO 45001) are successfully certified by Lloyd's Register.

The information in this publication reflects our level of technical knowledge and experience at the time of print of this product information. The information is provided by Kurita Europe GmbH at the best of its knowledge and in good faith. Within legal frameworks, it does not, however, constitute legal warranties, liabilities, covenants or such by Kurita Europe GmbH but are provided as guidance only. This is notably true in view of particular characteristics or of fitness for a specific purpose of the product. The above-mentioned information does not relieve the user of the product from the obligation of own examinations, appropriate precautionary measures and tests due to the abundance of possible influences during storage, manufacturing and application of the product – this is explicitly recommended by Kurita Europe GmbH. It shall be the responsibility of the recipient of our products to respect any intellectual property rights, existing laws and other provisions. If not explicitly regulated differently and in writing, the General Terms and Conditions of Kurita Europe GmbH are unaffected by this product information.

Headquarters:
Kurita Europe GmbH
Theodor-Heuss-Anlage 2
68165 Mannheim
Germany
Phone: +49 621 1218 3000
Fax: +49 621 1218 3600

Internet: www.kurita.eu
Email: kuritaeurope@kurita-water.com